

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/045899 A1

(51) International Patent Classification⁷: **B60N 2/36**
(21) International Application Number:
PCT/NL2003/000793
(22) International Filing Date:
11 November 2003 (11.11.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
1021937 16 November 2002 (16.11.2002) NL
(71) Applicant (for all designated States except US): IAC B.V.
[NL/NL]; Bloemendaallaan 84, NL-3771 HW Barneveld
(NL).
(72) Inventor; and
(75) Inventor/Applicant (for US only): BOONSTRA, Dirk
[NL/NL]; Bloemendaallaan 84, NL-3771 HW Barneveld
(NL).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR DETACHABLY FIXATING AN OBJECT



(57) Abstract: A device for detachably fixating a first object (2), e.g. a foldable car seat in folded position, to a second object (3), e.g. a vehicle, the device comprising an elastic cord (4), characterised in that the elastic cord (4) is connected, at at least one position, to a fastening means (6,7) by means of at least one pin (5), which pin (5) at least partially pierces the elastic cord (4) and preferably has a diameter of at most several millimetres. The invention further provides a method for the manufacture of a device for detachably fixating a first object (2), e.g. a foldable car seat in folded position, to a second object (3), e.g. a vehicle, the device comprising an elastic cord (4), characterised in that the elastic cord (4) is connected, at at least one position, to a fastening means (6,7) by at least partially piercing the elastic cord (4) with at least one pin (5), the pin (5) preferably having a diameter of at most several millimetres.

WO 2004/045899 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.